



## Enterprise-grade wireless presentation kit enabling native screen mirroring

Designed for large scale deployments and working through Miracast and Airplay protocol, the ScreenBeam 960 makes it easy to connect your Windows, Android or Apple device to the room display with a single click or swipe. Extended desktop frees up your device for other actions while presenting with both interactive touch displays and it is wireless touch supported.

Central Management System (CMS) software is included for remote management of receivers, providing enterprise-class security and manageability that IT departments need.

The kit contains the ScreenBeam 960A, a mounting bracket and a USB-power cable.

For more details, please click [HERE](#)

### 01 DEVICE

|                  |                                                                               |
|------------------|-------------------------------------------------------------------------------|
| Operating system | Windows 10, Android 4.2 (and later), macOS 10 (and later), iOS 11 (and later) |
| LAN (RJ45)       | x1                                                                            |
| VGA In           | x1                                                                            |
| VGA Out          | x1                                                                            |
| HDMI Out         | x1                                                                            |
| USB-touch        | x1                                                                            |
| Audio            | LCPM 2.0                                                                      |
| Rozlišení        | up to 1920x1080 @30Hz                                                         |
| Ethernet         | RJ45 10/100 LAN                                                               |
| Features         | touch support: 1 point, extended desktop with Windows OS                      |
| Language support | EN, DE, FR, PL, NL, RU, ES, IT, JP, CN, KO                                    |

### 02 SPECIFIKACE

|               |                                                       |
|---------------|-------------------------------------------------------|
| WiFi standard | Miracast P2P: 802.11ac; Infrastructure: 802.11a/b/g/n |
|---------------|-------------------------------------------------------|

### 03 POWER-MANAGEMENT

|                 |            |
|-----------------|------------|
| Napájecí zdroj: | externí    |
| Odběr energie:  | 5W typisch |

## 04 UDRŽITELNOST

Předpisy

CE, RoHS support, RED

## 05 ROZMĚRY / HMOTNOST

Rozměry výrobku

168 x 168 x 34.5mm

EAN code

4948570032396

## 06 ENVIRONMENTAL CONDITIONS

Rozsah provozní teploty

0°C - 40°C

Operation humidity

10% - 85%

Rozsah teploty v klidu

- 0°C - 70°C

Storage humidity

5% - 90%

*Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED