



Enterprise-grade wireless presentation kit enabling native screen mirroring

Designed for large scale deployments and working through Miracast and Airplay protocol, the ScreenBeam 960 makes it easy to connect your Windows, Android or Apple device to the room display with a single click or swipe. Extended desktop frees up your device for other actions while presenting with both interactive touch displays and it is wireless touch supported.

Central Management System (CMS) software is included for remote management of receivers, providing enterprise-class security and manageability that IT departments need.

The kit contains the ScreenBeam 960A, a mounting bracket and a USB-power cable.

For more details, please click <u>HERE</u>

01 DEVICE

| Operating system | Windows 10, Android 4.2 (and later), macOS 10 (and later), iOS 11 (and later) |
|---------------------|-------------------------------------------------------------------------------|
| LAN (RJ45) | x1 |
| VGA In | x1 |
| VGA Out | x1 |
| HDMI Out | x1 |
| USB-touch | x1 |
| Headphone connector | yes |
| Audio | LCPM 2.0 |
| Resolution | up to 1920x1080 @30Hz |
| Ethernet | RJ45 10/100 LAN |
| Features | touch support: 1 point, extended desktop with Windows OS |
| Language support | EN, DE, FR, PL, NL, RU, ES, IT, JP, CN, KO |

02 TECHNICAL SPECIFICATION

POWER MANAGEMENT

WiFi standard

Miracast P2P: 802.11ac; Infrastucture: 802.11a/b/g/n

03

Power supply unit

| Power usage | 5W typical |
|------------------------------|-----------------------|
| 04 SUSTAINABILITY | |
| Regulations | CE, RoHS support, RED |
| 05 DIMENSIONS / WEIGHT | |
| Product dimensions L x W x H | 168 x 168 x 34.5mm |
| EAN code | 4948570032396 |
| 06 ENVIRONMENTAL CONDITIONS | |

| Operation temperature range | 0°C - 40°C |
|-----------------------------|--------------|
| Operation humidity | 10% - 85% |
| Storage temperature range | - 0°C - 70°C |
| Storage humidity | 5% - 90% |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED